

## Firmware updating procedures for True-I system

1. Download and save the latest firmware available from the “Download Center” at [www.true-i.com](http://www.true-i.com) to a folder of your choice in your PC or an SD card.

2. Unzip the downloaded file

If successful, you will see the files named “hmbs200.bin” and “setup.hms”

3. If you have saved the files in your PC or other storage device, please copy and paste these files into the SD card.

4. Disconnect the power supply cable from true-I and make sure that the device is completely turned off.

5. Insert the SD card.

6. Reconnect the power supply cable to device

**\*\* PLEASE MAKE SURE THAT THE DEVICE IS IN AN UPRIGHT POSITION AT ALL TIME DURING THE PROCEDURE, OTHERWISE IT MAY ACTIVATE THE ACCELERATION SENSOR DURING THE UPDATING PROCESS**

7. You will see the LED turn orange this means that the device is updating the firmware.

8. Updating the firmware may take more than a minute

Please wait until the system reboots the device and the LED turns and remains red.

**\*\* DO NOT TURN OFF THE POWER AND DO NOT PRESS ANY BUTTONS WHILE FIRMWARE UPDATING IS IN PROGRESS.**

9. If firmware is updated successfully to the device, the “hmbs200.bin” file will be automatically deleted from the SD card and you will see two new folders in the SD card; “BLACKBOX” and “MOVIE”.